AKEMI®

according to 1907/2006/EC, Article 31

Printing date 18.02.2019 Version number 5 Revision: 18.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: **Akelux Polishing Paste**

· Article number: 62029

 1.2 Relevant identified uses of the substance or mixture and

uses advised against

No further relevant information available.

Application of the substance / the

Polishing agent/ Burnishing compound mixture

· 1.3 Details of the supplier of the safety data sheet

 Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH

> Lechstrasse 28 D 90451 Nürnberg

Tel. +49(0)911-642960 Fax. +49(0)911-644456 e-mail info@akemi.de

· Further information obtainable

from: · 1.4 Emergency telephone

number:

Laboratory

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

+44 (171) 635 91 91

National Poison Inform. Centre

Medical Toxicology Unit

Avalonley Road London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· Classification according to

Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008 Void Hazard pictograms Void Signal word Void

· Hazard-determining components

of labelling: Not applicable.

· Hazard statements Void

· Additional information: EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

Mixture of substances listed below with nonhazardous additions. Description:

Dangerous components:

CAS: 64741-65-7 Naphtha (petroleum), heavy alkylate

EINECS: 265-067-2 Index number: 649-275-00-4 Reg.nr.: 01-2119472146-39

Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413 12.5-25%

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 18.02.2019 Version number 5 Revision: 18.02.2019

Trade name: Akelux Polishing Paste

(Contd. of page 1) For the wording of the listed hazard phrases refer to section 16.

· Additional information:

SECTION 4: First aid measures

· 4.1 Description of first aid measures

 General information: Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation: Take affected persons into fresh air and keep quiet.

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for

transportation.

Immediately wash with water and soap and rinse thoroughly. After skin contact:

Rinse opened eye for several minutes under running water. Then consult a After eye contact:

· After swallowing: Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and

delayed

Breathing difficulty

Headache Dizziness Dizziness

Gastric or intestinal disorders

Danger of impaired breathing.

Unconsciousness

Nausea

· Information for doctor: Symptoms in intoxication with (aromatic) hydrocarbons (dosis letalis about 30 g)

a) In acute intoxication: headache, dizziness, euphoria, gastro-intestinal

dysfunction, state of excitement, coma.

b) In chronic intoxication: myelotoxic damage, fatigue, dizziness, emaciation,

cardiac palpitation after physical exercise, leucopenia, anemia, leukosis.

Hazards

· 4.3 Indication of any immediate medical attention and special

treatment needed

If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

· For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

· 5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

· Additional information Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage

system.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 18.02.2019 Version number 5 Revision: 18.02.2019

Trade name: Akelux Polishing Paste

(Contd. of page 2)

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective clothing.

• 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

• <u>6.4 Reference to other sections</u> See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols. Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Information about fire - and

explosion protection: Keep ignition sources away - Do not smoke.

Traces of flammable substances may collect in the steam chamber of enclosed

systems. Keep clear ofignition sources.

Fumes can combine with air to form an explosive mixture.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles: Store in a cool location.

Store only in the original receptacle.

· Information about storage in one

common storage facility:

Do not store together with oxidising and acidic materials. Do not store together with alkalis (caustic solutions).

· Further information about storage

conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from frost.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about

design of technical facilities: No further data; see item 7.

(Contd. on page 4)

AKEMI®

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2019 Version number 5 Revision: 18.02.2019

Trade name: Akelux Polishing Paste

(Contd. of page 3)

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the

workplace:

The product does not contain any relevant quantities of materials with critical

values that have to be monitored at the workplace. The lists valid during the making were used as basis.

· Additional information:

· 8.2 Exposure controls

· Personal protective equipment:

- General protective and hygienic

measures:

The usual precautionary measures are to be adhered to when handling

chemicals.

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Apply solvent resistant skin cream before starting work.

Do not eat, drink, smoke or sniff while working.

• Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of

intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter A/P2

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the

product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves

Butyl rubber, BR Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.75 \text{ mm}$

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of

the following materials:

Natural rubber, NR Leather gloves

Strong material gloves

· Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid Colour: White

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 18.02.2019 Version number 5 Revision: 18.02.2019

	Trade name:	Akelux	Polishing	Paste
--	-------------	--------	------------------	-------

<u> </u>	
	(Contd. of page 4)
· <u>Odour:</u>	Specific type
 Change in condition Melting point/freezing point: Initial boiling point and boiling range: 	Undetermined. 100 °C
· Flash point:	64 °C
· Ignition temperature:	354 °C
· Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits: Lower: Upper:	0.7 Vol % 6.5 Vol %
· Vapour pressure at 20 °C:	23 hPa
· Density at 20 °C:	0.93 g/cm³
Solubility in / Miscibility with water:	Insoluble.
 Viscosity: Dynamic: Kinematic at 20 °C: 	Not determined. 999 s (DIN 53211/4)
· Solvent separation test:	< 3 %
Solvent content: Organic solvents: Water: 9.2 Other information	24.9 % 60.0 % No further relevant information available.

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

10.2 Chemical stability
 Thermal decomposition / conditions to be avoided:

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions

Reacts with acids, alkalis and oxidising agents.

• 10.4 Conditions to avoid
• 10.5 Incompatible materials:

No further relevant information available.

No further relevant information available.

· 10.6 Hazardous decomposition

products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h >31.3 mg/l (rat)

64741-65-7 Naphtha (petroleum), heavy alkylate

Oral LD50 >6,000 mg/kg (rat)

(Contd. on page 6)



(Contd. of page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 5 Revision: 18.02.2019

Trade name: Akelux Polishing Paste

LD50 >3,000 mg/kg (rbt) Dermal

Inhalative LC50/4 h >7.8 mg/l (rat)

· Primary irritant effect:

Printing date 18.02.2019

· Skin corrosion/irritation Based on available data, the classification criteria are not met. · Serious eye damage/irritation Based on available data, the classification criteria are not met. · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

 Aquatic toxicity: No further relevant information available.

· 12.2 Persistence and

degradability No further relevant information available. · 12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes: Do not allow product to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly

hazardous for water

· 12.5 Results of PBT and vPvB assessment

Not applicable. · PBT: · vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

 Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

 European 	waste cata	logue	
12 00 00	WASTES		$C \coprod V$

WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF 12 00 00 METALS AND PLASTICS

12 01 00 wastes from shaping and physical and mechanical surface treatment of metals and plastics

12 01 09* machining emulsions and solutions free of halogens

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS 00 00 80 (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 12 waste paint and varnish other than those mentioned in 08 01 11

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

Non contaminated packagings may be reused.

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 18.02.2019 Version number 5 Revision: 18.02.2019

Trade name: Akelux Polishing Paste

(Contd. of page 6)

SECTION 14: Transport information

· 14.1 OIN-INUITIDEI	
· ADR, ADN, IMDG, IATA	Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

14.1 LINL Number

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

- UN "Model Regulation": Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed.

National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed.

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

. VOC EU 232.5 g/l

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
 H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

· Recommended restriction of use refer to Technical Data Sheet (TDS)

Department issuing SDS:Contact:LaboratoryElke Hake

Fon ++49 (0)911 64296-59 @mail E.Hake@akemi.de

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 8)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2019 Version number 5 Revision: 18.02.2019

Trade name: Akelux Polishing Paste

(Contd. of page 7)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

· * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC