

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2021

Version number 13

Revision: 04.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Stain Repellent Nano Effect**
- Article number: 11931, 11932/11933, 11934/11935, 11936, 11967
- UFI: FPVV-SCPV-G31X-03V4

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Protective impregnation

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
- Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

- Response: IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.

- Storage: Store in a well-ventilated place. Keep cool.
Store locked up.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS08

- Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C11-C12, Isoalkanes, <2% aromatics
Hydrocarbons, C11-C13, Isoalkanes, <2% aromatics
Hydrocarbons, C11-C14 isoalkanes, cycloalkanes, <2% aromatics
Naphtha (petroleum), heavy alkylate

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2021

Version number 13

Revision: 04.03.2021

Trade name: Stain Repellent Nano Effect

(Contd. of page 1)

- Hazard statements H304 May be fatal if swallowed and enters airways.
H413 May cause long lasting harmful effects to aquatic life.
- Precautionary statements P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P260 Do not breathe mist/vapours/spray.
P280 Wear protective gloves.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information: EUH066 Repeated exposure may cause skin dryness or cracking.
- **2.3 Other hazards** The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

EC number: 918-167-1 Reg.nr.: 01-2119472146-39-xxxx	Hydrocarbons, C11-C12, Isoalkanes, <2% aromatics Asp. Tox. 1, H304 Aquatic Chronic 4, H413	25-50%
EC number: 920-901-0 Reg.nr.: 01-2119456810-40-xxxx	Hydrocarbons, C11-C13, Isoalkanes, <2% aromatics Asp. Tox. 1, H304	12.5-25%
EC number: 927-285-2 Reg.nr.: 01-2119480162-45	Hydrocarbons, C11-C14 isoalkanes, cycloalkanes, <2% aromatics Asp. Tox. 1, H304	12.5-25%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	<12.5%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60-xxxx	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	1-5%
CAS: 64741-65-7 EINECS: 265-067-2 Index number: 649-275-00-4 Reg.nr.: 01-2119472146-39	Naphtha (petroleum), heavy alkylate Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413	1-5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General information: Take affected persons out into the fresh air.
Position and transport stably in side position.
Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: A person vomiting while laying on their back should be turned onto their side.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2021

Version number 13

Revision: 04.03.2021

Trade name: Stain Repellent Nano Effect· Information for doctor:

(Contd. of page 2)

Symptoms in intoxication with (aromatic) hydrocarbons (dosis letalis about 30 g)
 a) In acute intoxication: headache, dizziness, euphoria, gastro-intestinal dysfunction, state of excitement, coma.
 b) In chronic intoxication: myelotoxic damage, fatigue, dizziness, emaciation, cardiac palpitation after physical exercise, leucopenia, anemia, leukosis.
 Therapy in hydrocarbons intoxication: In case of inhalation provision of fresh air; in case of peroral intake administration of Carbo medicinalis; only after intubation conduct of gastrolavage in application of Carbo medicinalis; in case of cramps administration of Diazepam 20 mg intravenously.

· **4.2 Most important symptoms and effects, both acute and delayed**

Headache
 Dizziness
 Dizziness
 Nausea
 Gastric or intestinal disorders
 Cramp
 Danger of impaired breathing.

· Hazards

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed or in case of vomiting, danger of entering the lungs.
 If swallowed, gastric irrigation with added, activated carbon.
 Monitor circulation.

SECTION 5: Firefighting measures· **5.1 Extinguishing media**· Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.
 Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
 Carbon monoxide (CO)

· **5.3 Advice for firefighters**· Protective equipment:

Wear self-contained respiratory protective device.
 Do not inhale explosion gases or combustion gases.
 Wear fully protective suit.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
 Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation
 Use respiratory protective device against the effects of fumes/dust/aerosol.
 Keep away from ignition sources.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2021

Version number 13

Revision: 04.03.2021

Trade name: Stain Repellent Nano Effect

(Contd. of page 3)

- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.
Store in cool, dry place in tightly closed receptacles.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.

- Information about fire - and explosion protection:

Highly volatile, flammable constituents are released during processing.

- **7.2 Conditions for safe storage, including any incompatibilities**

- Storage:

- Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.
Provide solvent resistant, sealed floor.
Store only in the original receptacle.

- Information about storage in one common storage facility:

Store away from oxidising agents.
Store away from foodstuffs.

- Further information about storage conditions:

Store receptacle in a well ventilated area.

- Storage class:

10

- **7.3 Specific end use(s)**

No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- Additional information about design of technical facilities:

No further data; see item 7.

- Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

34590-94-8 Dipropylene glycol monomethyl ether

WEL Long-term value: 308 mg/m³, 50 ppm
Sk

- DNELs

123-86-4 n-butyl acetate

Oral	DNEL (Kurzzeit-akut)	2 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	11 mg/kg bw/day (ARB) 6 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	11 mg/kg bw/day (ARB) 6 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	960 mg/m ³ Air (ARB) 860 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	480 mg/m ³ Air (ARB) 102.34 mg/m ³ Air (BEV)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2021

Version number 13

Revision: 04.03.2021

Trade name: Stain Repellent Nano Effect

(Contd. of page 4)

34590-94-8 Dipropylene glycol monomethyl ether

Oral	DNEL (Langzeit-wiederholt)	1.67 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	65 mg/kg bw/day (ARB)
		15 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	310 mg/m ³ Air (ARB)
		37.2 mg/m ³ Air (BEV)

· PNECs**123-86-4 n-butyl acetate**

PNEC (wässrig)	35.6 mg/l (KA)
	0.018 mg/l (MW)
	0.18 mg/l (SW)
	0.36 mg/l (WAS)
PNEC (fest)	0.0903 mg/kg Trockengew (BO)
	0.0981 mg/kg Trockengew (MWS)
	0.981 mg/kg Trockengew (SWS)

34590-94-8 Dipropylene glycol monomethyl ether

PNEC (wässrig)	4,168 mg/l (KA)
	1.9 mg/l (MW)
	19 mg/l (SW)
PNEC (fest)	2.74 mg/kg Trockengew (BO)
	7.02 mg/kg Trockengew (MWS)
	70.2 mg/kg Trockengew (SWS)

· Additional information:

The lists valid during the making were used as basis.

· **8.2 Exposure controls**· Personal protective equipment:· General protective and hygienic measures:

Do not eat or drink while working.
 Apply solvent resistant skin cream before starting work.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Short term filter device:

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

After use of gloves apply skin-cleaning agents and skin cosmetics.

Preventive skin protection by use of skin-protecting agents is recommended.
 After each cleaning use treatment creams, for very dry skin greasy ointments.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Skin protection agent recommendation for preventive skin shelter without use of protective gloves:

STOKODERM (<http://www.stoko.com>)

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2021

Version number 13

Revision: 04.03.2021

Trade name: Stain Repellent Nano Effect

(Contd. of page 5)

STOKO EMULSION (<http://www.stoko.com>)

Skin protection recommendation for skin cleaning after product handling:

FRAPANTOL (<http://www.stoko.com>)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (<http://www.stoko.com>)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove materialValue for the permeation: Level ≤ 1 , 30 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Camatril (KCL, Art_No. 730, 731, 732, 733)

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art_No. 890)

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

Not suitable are gloves made of the following materials:

Chloroprene rubber, CR

Strong material gloves

Leather gloves

Natural rubber, NR

Eye protection:

Goggles recommended during refilling

Body protection:

Solvent resistant protective clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**General InformationAppearance:Form:

Fluid

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2021

Version number 13

Revision: 04.03.2021

Trade name: Stain Repellent Nano Effect

(Contd. of page 6)

· <u>Colour:</u>	Colourless
· <u>Odour:</u>	Characteristic
· <u>pH-value:</u>	Not applicable
· <u>Change in condition</u>	
<u>Melting point/freezing point:</u>	Undetermined. Not applicable
<u>Initial boiling point and boiling range:</u>	124 °C
· <u>Flash point:</u>	62 °C
· <u>Flammability (solid, gas):</u>	Not determined
· <u>Ignition temperature:</u>	370 °C
· <u>Auto-ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product does not present an explosion hazard.
· <u>Explosion limits:</u>	
<u>Lower:</u>	3 Vol %
<u>Upper:</u>	10.4 Vol %
· <u>Vapour pressure at 20 °C:</u>	10.7 hPa
· <u>Density at 20 °C:</u>	0.79 g/cm ³
· <u>Solubility in / Miscibility with water:</u>	Not miscible or difficult to mix.
· <u>Viscosity:</u>	
<u>Dynamic:</u>	Not determined.
<u>Kinematic at 20 °C:</u>	11 s (DIN 53211/4)
· <u>Solvent content:</u>	
<u>Organic solvents:</u>	94.4 %
<u>Solids content:</u>	3.1 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
Reacts with strong oxidising agents.
Reacts with acids.
Forms flammable gases/fumes.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide
Hydrogen fluoride

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2021

Version number 13

Revision: 04.03.2021

Trade name: Stain Repellent Nano Effect

(Contd. of page 7)

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	>333 mg/l (rat)
------------	----------	-----------------

Hydrocarbons, C11-C12, Isoalkanes, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)

Hydrocarbons, C11-C13, Isoalkanes, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4h	2.5 mg/m ³ (rat)
	LC50/8h	>5,000 ppm (rat)
	NOAEC	1,000 mg/l (rat)

Hydrocarbons, C11-C14 isoalkanes, cycloalkanes, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat)
	NOAEL-Werte	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	NOAEL	>10,400 mg/m ³ (rat)

123-86-4 n-butyl acetate

Oral	LD50	10,800 mg/kg (rat) (OECD 423)
Dermal	LD50	>17,600 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	>21 mg/l (rat) (OECD 403)
	LC50	390 mg/m ³ (rat)
	LC50/48h	64 mg/l (Brachydanio rerio)

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	5,383 mg/kg (rat)
	NOAEL	5,000 mg/kg (rat)
Dermal	LD50	5,001 mg/kg (rabbit)
		9,500 mg/kg (rat)
	NOEL	2,850 mg/kg (rabbit)
Inhalative	LC50/4 h	3,080 mg/l (rat)

64741-65-7 Naphtha (petroleum), heavy alkylate

Oral	LD50	>6,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rbt)
Inhalative	LC50/4 h	>7.8 mg/l (rat)

· Primary irritant effect:

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· Additional toxicological information:

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.

(Contd. on page 9)

-GB-

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2021

Version number 13

Revision: 04.03.2021

Trade name: Stain Repellent Nano Effect

(Contd. of page 8)

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:****Hydrocarbons, C11-C12, Isoalkanes, <2% aromatics**

EL0/48h	1,000 mg/l (daphnia magna)
EL0/72h	1,000 mg/l (Pseudokirchneriella subcapitata)
LL0/96h	1,000 mg/l (Oncorhynchus mykiss)
NOELR/72h	1,000 mg/l (Pseudokirchneriella subcapitata)
NOELR/21d	1 mg/l (daphnia magna)

Hydrocarbons, C11-C13, Isoalkanes, <2% aromatics

EC50/48h	>1,000 mg/l (daphnia magna)
ErC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
EL0/48h	1,000 mg/l (daphnia magna)
LL0/96h	1,000 mg/l (Oncorhynchus mykiss)
NOELR/72h	1,000 mg/l (Pseudokirchneriella subcapitata)
EC50/72h	>1,000 mg/l (green alge)
LC50/96h	>1,000 mg/l (Oncorhynchus mykiss)

Hydrocarbons, C11-C14 isoalkanes, cycloalkanes, <2% aromatics

EL50/72h	>1,000 mg/l (green alge)
LL50/96h	>1,000 mg/l (piscis)
NOELR/21d	1 mg/l (daphnia magna)
NOELR/28d	0.103 mg/l (piscis)

123-86-4 n-butyl acetate

EC50/24h	72.8 mg/l (daphnia magna) (DIN 38412)
EC50/96h	320 mg/l (green alge)
LC50/24h	205 mg/l (daphnia magna)
IC50/72h	648 mg/l (Desmodesmus subspicatus)
EC10/18h	959 mg/l (pseudomonas putida)
EC50/48h	44 mg/l (daphnia magna)
EC50/16h	959 mg/l (pseudomonas putida)
NOEC	200 mg/kg (Desmodesmus subspicatus)
NOEC/21d	23 mg/l (daphnia magna)
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest) 674 mg/l (Scenedesmus subspicatus)
LC50/96h	62 mg/l (Danio rerio.) 81 mg/l (piscis) 100 mg/l (Iepomis macrochirus) 62 mg/l (Leuciscus idus) (DIN 38412) 18 mg/l (Pimephales promelas) (OECD 203)

34590-94-8 Dipropylene glycol monomethyl ether

EC50/48h	1,919 mg/l (daphnia magna)
EC50/48h	1,919 mg/l (daphnia magna)
EC50/72h	>969 mg/l (green alge)
LC50/96h	>1,000 mg/l (piscis) >10,000 mg/l (Pimephales promelas)
LC50/72h	>150 mg/l (piscis)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2021

Version number 13

Revision: 04.03.2021

Trade name: Stain Repellent Nano Effect

(Contd. of page 9)

- **12.2 Persistence and degradability** No further relevant information available.
- Other information: The product is not easily biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- General notes: Do not allow product to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
- Recommended cleansing agents: Alcohol

SECTION 14: Transport information

- | | |
|--|--|
| · 14.1 UN-Number | |
| · <u>ADR, ADN, IMDG, IATA</u> | Void |
| · 14.2 UN proper shipping name | |
| · <u>ADR, ADN, IMDG, IATA</u> | Void |
| · 14.3 Transport hazard class(es) | |
| · <u>ADR, ADN, IMDG, IATA</u> | |
| · <u>Class</u> | Void |
| · 14.4 Packing group | |
| · <u>ADR, IMDG, IATA</u> | Void |
| · 14.5 Environmental hazards: | |
| · <u>Marine pollutant:</u> | No |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · <u>Transport/Additional information:</u> | Not dangerous according to the above specifications. |
| · <u>UN "Model Regulation":</u> | Void |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.03.2021

Version number 13

Revision: 04.03.2021

Trade name: Stain Repellent Nano Effect

(Contd. of page 10)

- National regulations:
- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- VOC EU 745.5 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H413 May cause long lasting harmful effects to aquatic life.
- Recommended restriction of use refer to Technical Data Sheet (TDS)
- Department issuing SDS: Laboratory
- Contact: Elke Hake
Fon ++49 (0)911 64296-59
@mail E.Hake@akemi.de
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4
- * Data compared to the previous version altered. Adaptation in accordance with REACH directive 1907/2006/EC
16.12.2019
- Datasheet created on:
- International Product Registration Status USA (Toxic Substances Control Act, TSCA)
J (Existing and New Chemical Substance List, ENCS)