

**Technical Data Sheet**

Page 1 of 1

<b>Properties:</b>	AKEMI® Techno Ceramic Daily Cleaner Spray is an acid- and lye-free ready-to-use cleaning spray made of surfactants, auxiliary materials, odoriferous substances and alcohols. The product is free from phosphates; the surfactants contained are biodegradable in correspondence with the legal regulations for surfactants.
<b>Application Area:</b>	AKEMI® Techno Ceramic Daily Cleaner is a fast drying cleaning spray and is especially suited for the daily and easy removal of light dirtying e.g. light films of oil and grease, dried drinks on large-size high-tech ceramic slabs, especially kitchen counter tops, displays, washstands, shelves etc. AKEMI® Daily Cleaner removes light traces of lime and is therefore very well suited for the application in shower rooms and on armatures. The surfaces are cleaned free of streaks.
<b>Instructions for Use:</b>	<ol style="list-style-type: none"><li>1. Open the spray nozzle.</li><li>2. Spray evenly on surfaces to be treated.</li><li>3. Clean surfaces with a clean, humid and absorbent cloth.</li></ol>
<b>Special Notes:</b>	<ul style="list-style-type: none"><li>- For adequate waste disposal container must be completely emptied.</li><li>- For deep dirtying apply AKEMI® Crystal Clean undiluted or depending on the kind of dirtying apply AKEMI® Techno Ceramic Intensive Cleaner, AKEMI® Algae and Moss Remover or AKEMI® Disinfectant Cleaner.</li><li>- For industrial use only.</li></ul>
<b>Technical Data:</b>	Coverage: approx. 10 – 20 m <sup>2</sup> /liter Colour: colourless Density: approx. 1.00 g/cm <sup>3</sup> pH value: approx. 7
<b>Storage:</b>	2 years if stored in cool place free from frost in its tightly closed original container.
<b>Health &amp; Safety:</b>	Read Material Safety Data Sheet before handling or using this product.
<b>Important Notice:</b>	The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 11.15