

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Akepox 4050 Anti-Slip Mix Component B**
- Article number: 10580B, 10581B, 10583B, 10587B, 10588B, 10589B, 10590B, 10591B, 11582
- UFI: VWH3-1086-C00S-JMCQ

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy coating
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
- Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

- Skin Corr. 1B H314 Causes severe skin burns and eye damage.
- Eye Dam. 1 H318 Causes serious eye damage.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS05 GHS07

Signal word

Danger

Hazard-determining components of labelling:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)
3-aminomethyl-3,5,5-trimethylcyclohexylamine
1,3-Benzenedimethanamine, reaction products with glycidyl tolyl ether
N-(3-(trimethoxysilyl)propyl)ethylenediamine
phenole, styrenated

Hazard statements

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: AkepoX 4050 Anti-Slip Mix Component B

(Contd. of page 1)

P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

- Results of PBT and vPvB assessment
- PBT: Not applicable.

· vPvB:

1760-24-3 | N-(3-(trimethoxysilyl)propyl)ethylenediamine

· Determination of endocrine-disrupting properties

61788-44-1	phenole, styrenated	List II
69-72-7	salicylic acid	List II; III

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-0000	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	<12.5%
CAS: 113930-69-1 NLP: 500-302-7 Reg.nr.: 01-2119965162-39	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Chronic 2, H411 Skin Sens. 1, H317	<10%
CAS: 90194-04-0 EINECS: 290-611-0 Reg.nr.: 01-2120770491-54	1,3-Benzenedimethanamine, reaction products with glycidyl tolyl ether Eye Dam. 1, H318 Aquatic Chronic 2, H411 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	1-5%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-0000	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	1-5%
CAS: 1760-24-3 EINECS: 217-164-6 Reg.nr.: 01-2119970215-39	N-(3-(trimethoxysilyl)propyl)ethylenediamine Eye Dam. 1, H318 Skin Sens. 1, H317; STOT SE 3, H335 vPvB	1-5%
CAS: 61788-44-1 EINECS: 262-975-0 Reg.nr.: 01-2119979575-18	phenole, styrenated Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317	1-5%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 2)

CAS: 69-72-7 EINECS: 200-712-3 Index number: 607-732-00-5 Reg.nr.: 01-2119486984-17	salicylic acid Repr. 2, H361d Eye Dam. 1, H318 Acute Tox. 4, H302	<1%
CAS: 103-83-3 EINECS: 203-149-1 Index number: 612-074-00-7 Reg.nr.: 01-2119529232-48-xxxx	benzyltrimethylammonium chloride Flam. Liq. 3, H226 Acute Tox. 3, H331 Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312 Aquatic Chronic 3, H412	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General information: Take affected persons out into the fresh air.
Position and transport stably in side position.
Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Nausea
Breathing difficulty
Coughing
Allergic reactions
Danger of impaired breathing.

4.3 Hazards**4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NO_x)
Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

- Protective equipment: Wear fully protective suit.
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 3)

- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
Use respiratory protective device against the effects of fumes/dust/aerosol.
- **6.2 Environmental precautions:** Do not allow to penetrate the ground/soil.
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose of the material collected according to regulations.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep receptacles tightly sealed.
Store in cool, dry place in tightly closed receptacles.
Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.
- Information about fire - and explosion protection: No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
Prevent any seepage into the ground.
- Information about storage in one common storage facility: Store away from oxidising agents.
Store away from foodstuffs.
- Further information about storage conditions: Store receptacle in a well ventilated area.
Keep container tightly sealed.
- Storage class: 8 A
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 4)

· DNELs**100-51-6 Benzyl alcohol**

Oral	DNEL (Kurzzeit-akut)	20 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	4 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	40 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	20 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	8 mg/kg bw/day (ARB)
		4 mg/kg bw/day (BEV)
	DNEL (Kurzzeit-akut)	110 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	27 mg/m ³ Air (BEV)
	22 mg/m ³ Air (ARB)	5.4 mg/m ³ Air (BEV)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	DNEL (Kurzzeit-akut)	0.3 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.3 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	0.073 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	0.073 mg/m ³ Air (ARB)

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

Oral	DNEL (Langzeit-wiederholt)	2.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	5 mg/kg bw/day (ARB)
		17 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	5 mg/kg bw/day (ARB)
		2.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	35.5 mg/m ³ Air (ARB)
		8.7 mg/m ³ Air (BEV)

61788-44-1 phenole, styrenated

Oral	DNEL (Langzeit-wiederholt)	1.562 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	6.25 mg/kg bw/day (ARB)
		3.125 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	11.02 mg/m ³ Air (ARB)
		2.717 mg/m ³ Air (BEV)

69-72-7 salicylic acid

Oral	DNEL (Kurzzeit-akut)	4 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	1 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (ARB)
		1 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	16 mg/m ³ Air (ARB)
		0.2-4 mg/m ³ Air (BEV)

103-83-3 benzyldimethylamine

Oral	DNEL (Kurzzeit-akut)	0.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.25 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	2.8 mg/kg bw/day (ARB)
		1 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	1.4 mg/kg bw/day (ARB)
		0.5 mg/kg bw/day (BEV)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 5)

Inhalative	DNEL (Kurzzeit-akut)	9.9 mg/m ³ Air (ARB) 1.74 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	1-14.6 mg/m ³ Air (ARB) 0.87 mg/m ³ Air (BEV)

· PNECs

100-51-6 Benzyl alcohol

PNEC (wässrig)	39 mg/l (KA)
	0.1 mg/l (MW)
	1 mg/l (SW)
	2.3 mg/l (WAS)
PNEC (fest)	0.456 mg/kg Trockengew (BO)
	0.527 mg/kg Trockengew (MWS)
	5.27 mg/kg Trockengew (SWS)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

PNEC (wässrig)	3.18 mg/l (KA)
	0.006 mg/l (MW)
	0.06 mg/l (SW)
	0.23 mg/l (WAS)
PNEC (fest)	1.121 mg/kg Trockengew (BO)
	0.578 mg/kg Trockengew (MWS)
	5.784 mg/kg Trockengew (SWS)

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

PNEC (wässrig)	25 mg/l (KA)
	0.0062 mg/l (MW)
	0.062 mg/l (SW)
	0.62 mg/l (WAS)
PNEC (fest)	0.0075 mg/kg Trockengew (BO)
	0.005 mg/kg Trockengew (MWS)
	0.05 mg/kg Trockengew (SWS)

61788-44-1 phenole, styrenated

PNEC (wässrig)	0.17 mg/l (KA)
	0 mg/l (MW)
	0.001 mg/l (SW)
PNEC (fest)	31.525 mg/kg Trockengew (BO)
	65.778 mg/kg Trockengew (MWS)
	65.778 mg/kg Trockengew (SWS)

69-72-7 salicylic acid

PNEC (wässrig)	162 mg/l (KA)
	0.02 mg/l (MW)
	0.2 mg/l (SW)
PNEC (fest)	0.166 mg/kg Trockengew (BO)
	0.142 mg/kg Trockengew (MWS)
	1.42 mg/kg Trockengew (SWS)

103-83-3 benzyl dimethylamine

PNEC (wässrig)	534 mg/l (KA)
----------------	---------------

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 6)

PNEC (fest)	0.00048 mg/l (MW)
	0.0048 mg/l (SW)
	0.0114 mg/kg Trockengew (BO)
	0.0071 mg/kg Trockengew (MWS)
	0.071 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Clean skin thoroughly immediately after handling the product.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Respiratory protection:

Short term filter device:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (<http://www.stoko.com>)

Skin protection recommendation for skin cleaning after product handling:

Kresto Classic (<http://debstoko.com>)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (<http://www.stoko.com>)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 7)

- As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material Value for the permeation: Level \leq 6, 480 min
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
 - For the permanent contact gloves made of the following materials are suitable:
Butyl rubber, BR
Butoject (KCL, Art_No. 897, 898)
Nitrile rubber, NBR
Camatril (KCL, Art_No. 730, 731, 732, 733)
Dermatril (Art_No. 740, 741, 742)
 - As protection from splashes gloves made of the following materials are suitable:
Butyl rubber, BR
Butoject (KCL, Art_No. 897, 898)
Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
Chloroprene rubber, CR
Camapren (KCL, Art_No. 720, 722, 726)
 - Not suitable are gloves made of the following materials:
Natural rubber, NR
Fluorocarbon rubber (Viton)
Leather gloves
Strong material gloves
 - Eye/face protection
 Tightly sealed goggles
 - Body protection:
Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- General Information
- Colour: Dark grey
- Odour: Characteristic
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range >200 °C
- Lower and upper explosion limit
- Lower: 1.3 Vol %
- Upper: 13 Vol %
- Flash point: >100 °C
- Auto-ignition temperature: 435 °C
- Decomposition temperature: > 200 °C
- pH Not determined.
Not applicable
- Viscosity:
- Kinematic viscosity Not determined.
- Dynamic at 20 °C: 85,000 mPas
- Solubility
- water: Not miscible or difficult to mix.
- Vapour pressure at 20 °C: 0.1 hPa

(Contd. on page 9)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: AkepoX 4050 Anti-Slip Mix Component B

(Contd. of page 8)

· Density and/or relative density
 · Density at 20 °C: 1.96 g/cm³

9.2 Other information

· Appearance:
 · Form: Pasty
 · Important information on protection of health and environment, and on safety.
 · Ignition temperature: Product is not selfigniting.
 · Explosive properties: Product does not present an explosion hazard.
 · Solvent content:
 · Organic solvents: 13.7 %
 · Solids content: 75.8 %

· Information with regard to physical hazard classes

· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Void
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Void
· <u>Flammable solids</u>	Void
· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	Void
· <u>Substances and mixtures, which emit flammable gases in contact with water</u>	Void
· <u>Oxidising liquids</u>	Void
· <u>Oxidising solids</u>	Void
· <u>Organic peroxides</u>	Void
· <u>Corrosive to metals</u>	Void
· <u>Desensitised explosives</u>	Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
 · **10.2 Chemical stability**
 · Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
 · **10.3 Possibility of hazardous reactions** Strong exothermic reaction with acids.
 Reacts with strong oxidising agents.
 · **10.4 Conditions to avoid** No further relevant information available.
 · **10.5 Incompatible materials:** No further relevant information available.
 · **10.6 Hazardous decomposition products:** Corrosive gases/vapours

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
 · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	4,336 mg/kg
------	------	-------------

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 9)

Dermal	LD50	16,290 mg/kg
Inhalative	LC50/4 h	>30.9 mg/l (rat)

100-51-6 Benzyl alcohol

Oral	LD50	1,040 mg/kg (mouse) 1,040 mg/kg (rabbit) 1,620 mg/kg (rat)
	NOEL	400 mg/kg (rat)
	NOAEL	200 mg/kg (mouse) 400 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/8h	1,000 ppm (rat)
	LC50/4 h	>4.178 mg/l (rat) (OECD 403)
	LC50/48h	360 mg/l (daphnia magna) 645 mg/l (goo)

113930-69-1 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)

Oral	NOAEL	10 mg/kg (rat)
------	-------	----------------

90194-04-0 1,3-Benzenedimethanamine, reaction products with glycidyl tolyl ether

Oral	LD50	500 mg/kg (ATE)
	NOAEL	15 mg/kg (rat)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	LD50	1,030 mg/kg (ATE) 1,030 mg/kg (rat)
	NOAEL-Werte	>250 mg/kg (rat)
Dermal	LD50	1,840 mg/kg (rabbit) >2,000 mg/kg (rat)
Inhalative	LC50/4 h	>5.01 mg/l (rat)

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

Oral	LD50	2,995 mg/kg (rat)
	NOEL	≥500 mg/kg (rat) (OECD 422)
	NOAEL	≥500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	1.49 mg/l (rat)

61788-44-1 phenole, styrenated

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>5,010 mg/kg (rabbit)
		>2,000 mg/kg (rat)
Inhalative	LC50/4 h	158.3 mg/l (rat)

69-72-7 salicylic acid

Oral	LD50	891 mg/kg (rat)
	NOAEL-Werte	250 mg/kg (rat) (OECD 416)
Dermal	LD50	>2,000 mg/kg (rabbit)
	LC50/48h	90 mg/l (Leuciscus idus)

103-83-3 benzyl dimethylamine

Oral	LD50	579 mg/kg (rat)
------	------	-----------------

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 10)

Dermal	NOAEL-Werte	150 mg/kg (rat) (OECD 407)
	LD50	1,660 mg/kg (rabbit)
Inhalative	LD50	1,660 µl/kg (rabbit)
	LC50/4 h	2.06 mg/l (rat)
	LC50	2,052 mg/m ³ (rat)

- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· <u>Endocrine disrupting properties</u>		
61788-44-1	phenole, styrenated	List II
69-72-7	salicylic acid	List II; III

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****100-51-6 Benzyl alcohol**

EC50/24h	55-400 mg/l (daphnia magna)
EC50/96h	640 mg/l (Scenedesmus pluvialis)
EC50	2,100 mg/l (BES) (OECD 209)
	79 mg/l (Scenedesmus quadricauda)
EC10/16h	658 mg/l (pseudomonas putida)
EC50/48h	230 mg/l (daphnia magna) (OECD 202)
ErC50/72h	770 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC0	640 mg/l (Scenedesmus quadricauda)
	658 mg/l (pseudomonas putida)
EC50/30min	71.4 mg/l (Photobac. phosphoreum)
	400 mg/l (pseudomonas putida)
IC5/96h	640 mg/l (Scenedesmus quadricauda)
NOEC	310 mg/kg (Pseudokirchneriella subcapitata) (OECD 201)
NOEC/21d	51 mg/l (daphnia magna) (OECD211)
EC50/72h	770 mg/l (algae) (OECD 201)
	500 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC50/96h	645 mg/l (goo)
	10 mg/l (Iepomis macrochirus)
	8.9 mg/l (Oncorhynchus mykiss)
	460 mg/l (Pimephales promelas) (EPA OPP 72-1)

113930-69-1 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)

EC50	888.9 mg/l (BES)
------	------------------

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 11)

EL50/48h	1.46 mg/l (daphnia magna)
EL50/72h	>30 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	64 mg/l (Oncorhynchus mykiss)

90194-04-0 1,3-Benzenedimethanamine, reaction products with glycidyl tolyl ether

EL50/48h	3.9 mg/l (daphnia magna)
EL50/72h	1.1 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	1.1 mg/l (Oncorhynchus mykiss)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC50/24h	44 mg/l (daphnia magna)
LC 0/96h	70 mg/l (piscis)
EC10/18h	1,120 mg/l (pseudomonas putida)
EC50/48h	23 mg/l (daphnia magna) (OECD TG 202)
ErC50/72h	>50 mg/l (Scenedesmus subspicatus) (EG 88/302)
NOEC/21d	3 mg/l (daphnia magna) (OECD 202)
EC10	11.2 mg/l (Desmodesmus subspicatus)
EC50/72h	37 mg/l (algae) (EG 88/302)
	>50 mg/l (Desmodesmus subspicatus)
	37 mg/l (Scenedesmus subspicatus)
LC50/96h	110 mg/l (Brachydanio rerio) (EG 84/449)
	110 mg/l (Leuciscus idus) (EG 84/449)

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

EC50	435 mg/l (Klärschlamm: Atmungs-/Vermehrungshemmung)
	67 mg/l (pseudomonas putida) (DIN 38412 part 8)
IC50/72h	8.8 mg/l (algae) (OECD 201)
EC50/48h	81 mg/l (daphnia magna)
ErC50/72h	8.8 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50/16h	67 mg/l (pseudomonas putida)
NOEC	3.1 mg/kg (algae) (OECD 201)
	≥1,000 mg/kg (Eisenia fetida (Regenwürmer)) (OECD 207)
NOELR/72h	3.1 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC/21d	>1 mg/l (daphnia magna)
EC50/48h	87.4 mg/l (daphnia magna)
EC50/72h	5 mg/l (algae)
	126 mg/l (Scenedesmus subspicatus)
LC50/96h	344 mg/l (Brachydanio rerio)
	597 mg/l (Danio rerio.)
	168 mg/l (pimephales promelas)

61788-44-1 phenole, styrenated

EC50	362 mg/l (BES)
	3.8 mg/l (piscis)
EL50/48h	4.6 mg/l (daphnia magna)
EL50/72h	20.42 mg/l (CHV)
	3.14 mg/l (Scenedesmus subspicatus)
LL50/96h	24 mg/l (Danio rerio.)
	14.8 mg/l (piscis)

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 12)

NOEC/21d	0.2 mg/l (daphnia magna)
EC50/72h	9.7 mg/l (algae)
LC50/96h	5.6 mg/l (Brachydanio rerio)

69-72-7 salicylic acid

EC50	380 mg/l (BES) (OECD 209)
LC50/24h	105-230 mg/l (daphnia magna)
EC50/48h	870 mg/l (daphnia magna) (OECD 202)
EC50/16h	380 mg/l (bacteria)
NOEC/21d	10 mg/l (daphnia magna) (OECD 202 II)
EC50/72h	>100 mg/l (algae) (OECD 201)
LC50/96h	1,370 mg/l (piscis) (OECD 203)
	1,380 mg/l (pimephales promelas)

103-83-3 benzyldimethylamine

EC5/16h	749.6 mg/l (bacteria) (DIN 38412 Part.8)
EC10/16h	534 mg/l (bacteria) (DIN 38412 Part 8)
EC50/48h	>100 mg/l (daphnia magna) (EU EC C.2)
ErC50/72h	1.34 mg/l (algae) (EU EC C.3)
NOEC/21d	0.789 mg/l (daphnia magna)
LC50/96h	37.8 mg/l (piscis) (OECD 203)
	38 mg/l (Leuciscus idus)

· **12.2 Persistence and****degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**· **PBT:**

Not applicable.

· **vPvB:**

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**· **Remark:**

Harmful to fish

· **Additional ecological information:**· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

SECTION 13: Disposal considerations· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

(Contd. on page 14)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 13)

- Uncleaned packaging:
- Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
- Recommended cleansing agents: Alcohol

SECTION 14: Transport information

- **14.1 UN number or ID number**
- ADR, IMDG, IATA UN2735

- **14.2 UN proper shipping name**
- ADR 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE)
- IMDG, IATA POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE)

- **14.3 Transport hazard class(es)**

- ADR



- Class 8 (C7) Corrosive substances.
- Label 8

- IMDG, IATA



- Class 8 Corrosive substances.
- Label 8

- **14.4 Packing group**

- ADR, IMDG, IATA II

- **14.5 Environmental hazards:**

- Marine pollutant: No

- **14.6 Special precautions for user**

- Hazard identification number (Kemler code): Warning: Corrosive substances. 80
- EMS Number: F-A,S-B
- Segregation groups (SGG18) Alkalis
- Stowage Category A
- Segregation Code SG35 Stow "separated from" SGG1-acids

- **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

- Transport/Additional information:

- ADR
- Limited quantities (LQ) 1L
- Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- Transport category 2

(Contd. on page 15)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 14)

· <u>Tunnel restriction code</u>	E
· <u>IMDG</u>	1L
· <u>Limited quantities (LQ)</u>	Code: E2
· <u>Excepted quantities (EQ)</u>	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <u>UN "Model Regulation":</u>	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE), 8, II

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 268.3 g/l

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Department issuing SDS: Laboratory

(Contd. on page 16)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 3 (replaces version 2)

Revision: 25.01.2024

Trade name: Akepox 4050 Anti-Slip Mix Component B

(Contd. of page 15)

<ul style="list-style-type: none"> · <u>Date of previous version:</u> · <u>Version number of previous version:</u> · <u>Abbreviations and acronyms:</u> 	<p>26.07.2022</p> <p>2</p> <p>RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)</p> <p>ICAO: International Civil Aviation Organisation</p> <p>ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)</p> <p>IMDG: International Maritime Code for Dangerous Goods</p> <p>IATA: International Air Transport Association</p> <p>GHS: Globally Harmonised System of Classification and Labelling of Chemicals</p> <p>EINECS: European Inventory of Existing Commercial Chemical Substances</p> <p>ELINCS: European List of Notified Chemical Substances</p> <p>CAS: Chemical Abstracts Service (division of the American Chemical Society)</p> <p>DNEL: Derived No-Effect Level (REACH)</p> <p>PNEC: Predicted No-Effect Concentration (REACH)</p> <p>LC50: Lethal concentration, 50 percent</p> <p>LD50: Lethal dose, 50 percent</p> <p>PBT: Persistent, Bioaccumulative and Toxic</p> <p>SVHC: Substances of Very High Concern</p> <p>vPvB: very Persistent and very Bioaccumulative</p> <p>ATE: Acute toxicity estimate values</p> <p>Flam. Liq. 3: Flammable liquids – Category 3</p> <p>Acute Tox. 4: Acute toxicity – Category 4</p> <p>Acute Tox. 3: Acute toxicity – Category 3</p> <p>Skin Corr. 1B: Skin corrosion/irritation – Category 1B</p> <p>Skin Irrit. 2: Skin corrosion/irritation – Category 2</p> <p>Eye Dam. 1: Serious eye damage/eye irritation – Category 1</p> <p>Eye Irrit. 2: Serious eye damage/eye irritation – Category 2</p> <p>Skin Sens. 1: Skin sensitisation – Category 1</p> <p>Skin Sens. 1A: Skin sensitisation – Category 1A</p> <p>Repr. 2: Reproductive toxicity – Category 2</p> <p>STOT SE 3: Specific target organ toxicity (single exposure) – Category 3</p> <p>Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2</p> <p>Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3</p>
--	---

EU