

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **Marble Filler 1000 Transparent Waterclear**

Article number: 10720, 10721

UFI: AD53-60S0-A00F-WV92

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Polyester resin

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg

Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de

Further information obtainable from:

Laboratory

#### 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH  
Tel. +49(0)911-64296-59  
Reachable during the following office hours:  
Monday – Thursday from 07:30 a.m. to 16:30 p.m.  
Friday from 07:30 a.m. to 13:30 p.m.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 2	H361d	Suspected of damaging the unborn child.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 1	H372	Causes damage to the hearing organs through prolonged or repeated exposure.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

styrene  
maleic anhydride  
poly(oxy-1,2-ethanediyl),  $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-

Hazard statements

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

### Trade name: Marble Filler 1000 Transparent Waterclear

(Contd. of page 1)

<ul style="list-style-type: none"> <li>· <u>Precautionary statements</u></li> </ul>	<p>H361d Suspected of damaging the unborn child.  H335 May cause respiratory irritation.  H372 Causes damage to the hearing organs through prolonged or repeated exposure.  H412 Harmful to aquatic life with long lasting effects.</p> <p>P101 If medical advice is needed, have product container or label at hand.  P102 Keep out of reach of children.  P103 Read carefully and follow all instructions.  P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  P260 Do not breathe vapours.  P273 Avoid release to the environment.  P280 Wear protective gloves / eye protection.  P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  P312 Call a POISON CENTER/doctor if you feel unwell.  P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  P403+P233 Store in a well-ventilated place. Keep container tightly closed.  P405 Store locked up.  P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p>
<ul style="list-style-type: none"> <li>· <b>2.3 Other hazards</b></li> <li>· Results of PBT and vPvB assessment</li> <li>· PBT: Not applicable.</li> <li>· vPvB: Not applicable.</li> <li>· <u>Determination of endocrine-disrupting properties</u></li> </ul>	<p>For information on endocrine disrupting properties see section 11.</p>

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- Description: Mixture of substances listed below with nonhazardous additions.

- Dangerous components:

CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32	styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119555267-33	xylene (mix) Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	<1%

(Contd. on page 3)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name: Marble Filler 1000 Transparent Waterclear**

(Contd. of page 2)

CAS: 3164-85-0 EINECS: 221-625-7 Index number: 607-230-00-6 Reg.nr.: 01-2119980714-29	Kalium-2-ethylhexanoat Repr. 1B, H360D Eye Dam. 1, H318 Skin Irrit. 2, H315	<1%
CAS: 104810-47-1 ELINCS: 400-830-7 Index number: 607-176-00-3 Reg.nr.: 01-2119396032-43 01-0000015075-76-xxxx	poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]- Aquatic Chronic 2, H411 Skin Sens. 1, H317	<1%
CAS: 108-31-6 EINECS: 203-571-6 Index number: 607-096-00-9 Reg.nr.: 01-2119472428-31	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372 Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1A, H317 EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

- General information: Take affected persons out into the fresh air. Position and transport stably in side position. Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: If skin irritation continues, consult a doctor.
- After eye contact: Immediately wash with water and soap and rinse thoroughly. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: A person vomiting while laying on their back should be turned onto their side.

#### · 4.2 Most important symptoms and effects, both acute and delayed

Headache  
Dizziness  
Dizziness  
Breathing difficulty  
Nausea

#### · Hazards

Danger of impaired breathing.

#### · 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

- Suitable extinguishing agents: CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name: Marble Filler 1000 Transparent Waterclear**

(Contd. of page 3)

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.  
In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· **5.3 Advice for firefighters**

· Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Mount respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

\* **SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

\* **SECTION 7: Handling and storage**

· **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground.

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name: Marble Filler 1000 Transparent Waterclear**

(Contd. of page 4)

- Information about storage in one common storage facility: Store away from oxidising agents.  
Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

- Ingredients with limit values that require monitoring at the workplace:

**1330-20-7 xylene (mix)**

IOELV	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin
-------	--

- DNELs

**100-42-5 styrene**

Oral	DNEL (Langzeit-wiederholt)	2.1 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	406 mg/kg bw/day (ARB)
		343 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289-306 mg/m <sup>3</sup> Air (ARB)
		174.25-182.75 mg/m <sup>3</sup> Air (BEV)
		DNEL (Langzeit-wiederholt)
		10.2 mg/m <sup>3</sup> Air (BEV)

**1330-20-7 xylene (mix)**

Oral	DNEL (Langzeit-wiederholt)	12.5 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	212 mg/kg bw/day (ARB)
		125 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	442 mg/m <sup>3</sup> Air (ARB)
		260 mg/m <sup>3</sup> Air (BEV)
		DNEL (Langzeit-wiederholt)
		65.3 mg/m <sup>3</sup> Air (BEV)

**104810-47-1 poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3-(2H- benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-**

Oral	DNEL (Langzeit-wiederholt)	0.025 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	0.5 mg/kg bw/day (ARB)
		0.25 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	0.35 mg/m <sup>3</sup> Air (ARB)
		0.085 mg/m <sup>3</sup> Air (BEV)

**108-31-6 maleic anhydride**

Oral	DNEL (Langzeit-wiederholt)	0.06 mg/kg bw/day (BEV)	
Dermal	DNEL (Kurzzeit-akut)	0.04 mg/kg bw/day (ARB)	
		DNEL ( Langzeit-wiederholt)	0.2 mg/kg bw/day (ARB)
		0.1 mg/kg bw/day (BEV)	
Inhalative	DNEL (Kurzzeit-akut)	0.8 mg/m <sup>3</sup> Air (ARB)	
		DNEL (Langzeit-wiederholt)	0.4 mg/m <sup>3</sup> Air (ARB)

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name: Marble Filler 1000 Transparent Waterclear**

(Contd. of page 5)

0.08 mg/m<sup>3</sup> Air (BEV)· **PNECs****100-42-5 styrene**

PNEC (wässrig)	5 mg/l (KA)
	0.014 mg/l (MW)
	0.028 mg/l (SW)
PNEC (fest)	0.04 mg/l (WAS)
	0.2 mg/kg Trockengew (BO)
	0.307 mg/kg Trockengew (MWS)
	0.614 mg/kg Trockengew (SWS)

**1330-20-7 xylene (mix)**

PNEC (wässrig)	6.58 mg/l (KA)
	0.327 mg/l (MW)
	0.327 mg/l (SW)
PNEC (fest)	0.327 mg/l (WAS)
	2.31 mg/kg Trockengew (BO)
	12.46 mg/kg Trockengew (MWS)
	12.46 mg/kg Trockengew (SWS)

**104810-47-1 poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-**

PNEC (wässrig)	10 mg/l (KA)
	0.00023 mg/l (MW)
	0.0023 mg/l (SW)
PNEC (fest)	0.028 mg/l (WAS)
	2 mg/kg Trockengew (BO)
	0.306 mg/kg Trockengew (MWS)
	3.06 mg/kg Trockengew (SWS)

**108-31-6 maleic anhydride**

PNEC (wässrig)	44.6 mg/l (KA)
	0.0043 mg/l (MW)
	0.043 mg/l (SW)
PNEC (fest)	0.4281 mg/l (WAS)
	0.042 mg/kg Trockengew (BO)
	0.0334 mg/kg Trockengew (MWS)
	0.334 mg/kg Trockengew (SWS)

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**

Use skin protection cream for skin protection.  
 Be sure to clean skin thoroughly after work and before breaks.  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Do not inhale gases / fumes / aerosols.  
 Avoid contact with the eyes and skin.

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

### Trade name: Marble Filler 1000 Transparent Waterclear

(Contd. of page 6)

- Respiratory protection: Filter A/P2  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
  - Hand protection  
Preventive skin protection by use of skin-protecting agents is recommended. After use of gloves apply skin-cleaning agents and skin cosmetics. Skin protection agent recommendation for preventive skin shelter without use of protective gloves:  
ARRETIL (<http://www.stoko.com>)  
Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:  
STOKODERM (<http://www.stoko.com>)  
Skin protection recommendation for skin cleaning after product handling:  
Kresto Classic (<http://debstoko.com>)  
Skin protection agent recommendation for skin aftercare:  
STOKO VITAN (<http://www.stoko.com>)  
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.  
This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).
- 

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves  
Fluorocarbon rubber (Viton)  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
  - Penetration time of glove material  
Value for the permeation: Level ≤ 6, 480 min  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
  - For the permanent contact gloves made of the following materials are suitable:  
Fluorocarbon rubber (Viton)  
Vitoject (KCL, Art\_No. 890)
  - As protection from splashes gloves made of the following materials are suitable:  
Fluorocarbon rubber (Viton)  
Vitoject (KCL, Art\_No. 890)  
Butyl rubber, BR  
Butoject (KCL, Art\_No. 897, 898)  
Nitrile rubber, NBR

(Contd. on page 8)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name: Marble Filler 1000 Transparent Waterclear**

(Contd. of page 7)

· Not suitable are gloves made of the following materials:

Camatril (KCL, 730, 731, 732, 733)

Chloroprene rubber, CR  
Natural rubber, NR  
Leather gloves  
Strong material gloves

· Eye/face protection



Tightly sealed goggles

· Body protection:

Protective work clothing

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

##### General Information

· <u>Colour:</u>	Colourless
· <u>Odour:</u>	Characteristic
· <u>Melting point/freezing point:</u>	Undetermined.
· <u>Boiling point or initial boiling point and boiling range</u>	145.2 °C (100-42-5 styrene)
· <u>Lower and upper explosion limit</u>	
· <u>Lower:</u>	1.2 Vol % (100-42-5 styrene)
· <u>Upper:</u>	8.9 Vol % (100-42-5 styrene)
· <u>Flash point:</u>	31 °C (100-42-5 styrene)
· <u>Auto-ignition temperature:</u>	480 °C (100-42-5 styrene)
· <u>pH</u>	Not determined. Not applicable
· <u>Viscosity:</u>	
· <u>Kinematic viscosity at 20 °C</u>	220 s (DIN 53211/4)
· <u>Dynamic:</u>	Not determined.
· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Vapour pressure at 20 °C:</u>	6 hPa (100-42-5 styrene)
· <u>Vapour pressure at 50 °C:</u>	35 hPa
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	1.13 g/cm <sup>3</sup>

#### 9.2 Other information

· <u>Appearance:</u>	
· <u>Form:</u>	Fluid
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <u>Solvent content:</u>	
· <u>Organic solvents:</u>	35.5 %
· <u>Solids content:</u>	62.0 %

#### Information with regard to physical hazard classes

· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Void
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Flammable liquid and vapour.
· <u>Flammable solids</u>	Void

(Contd. on page 9)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name: Marble Filler 1000 Transparent Waterclear**

(Contd. of page 8)

· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

**SECTION 10: Stability and reactivity**

· <b>10.1 Reactivity</b>	No further relevant information available.
· <b>10.2 Chemical stability</b>	
· Thermal decomposition / conditions to be avoided:	No decomposition if used and stored according to specifications.
· <b>10.3 Possibility of hazardous reactions</b>	Exothermic polymerisation. Reacts with peroxides and other radical forming substances. Reacts with strong alkali. Reacts with strong acids.
· <b>10.4 Conditions to avoid</b>	No further relevant information available.
· <b>10.5 Incompatible materials:</b>	No further relevant information available.
· <b>10.6 Hazardous decomposition products:</b>	No dangerous decomposition products known.

**SECTION 11: Toxicological information**

· <b>11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008</b>	
· Acute toxicity	Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

**ATE (Acute Toxicity Estimates)**

Inhalative LC50/4 h 34.3 mg/l (rat)

**100-42-5 styrene**

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)
Inhalative	LC50/4h	9.5 mg/m <sup>3</sup> (mouse)
		11,800 mg/m <sup>3</sup> (rat)
	LC50/4 h	11.8 mg/l (rat)
	NOAEC	4.34 mg/l (rat)

**1330-20-7 xylene (mix)**

Oral	LD50	3,523-4,300 mg/kg (rat)
Dermal	LD50	>4,200 mg/kg (rabbit)
Inhalative	LC50/4h	29,000 mg/m <sup>3</sup> (rat)
	LC50/4 h	21.7 mg/l (rat)
	LC50/48h	86 mg/l (Leuciscus idus)

(Contd. on page 10)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name:** Marble Filler 1000 Transparent Waterclear

(Contd. of page 9)

**104810-47-1 poly(oxy-1,2-ethanediyl),  $\alpha$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]- $\omega$ -[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

**108-31-6 maleic anhydride**

Oral	LD50	1,090-2,620 mg/kg (rabbit) (OECD 401)
		400-480 mg/kg (rat)
Dermal	LD50	2,620 mg/kg (rabbit)
Inhalative	LC50/1h	>4.35 mg/l (rat)
	LC50/48h	138 mg/l (lem)

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Suspected of damaging the unborn child.
- STOT-single exposure May cause respiratory irritation.
- STOT-repeated exposure Causes damage to the hearing organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

- Endocrine disrupting properties

None of the ingredients is listed.

**SECTION 12: Ecological information****12.1 Toxicity**

- Aquatic toxicity:

**100-42-5 styrene**

EC50/96h	6.3 mg/l (Pseudokirchneriella subcapitata)
EC50	500 mg/l (BES) (ISO Vorschrift 8192-1986 E)
	5.5 mg/l (Photobac. phosphoreum)
IC50/72h	4.9 mg/l (algae)
	1.4 mg/l (selenastrum capricornutum)
IC5/8d	>200 mg/l (Scenedesmus quadricauda)
EC10/16h	72 mg/l (pseudomonas putida)
EC50/16h	>72 mg/l (pseudomonas putida)
EC50/8d	>200 mg/l (Scenedesmus quadricauda)
EC50/72u	>1-<10 mg/l (algae)
EC20/0.5h	140 mg/l (BES) (OECD 209)
NOEC/21d	1.01 mg/l (daphnia magna)
EC10	0.28 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050)
EC50/48h	0.56 mg/l (algae)
	3.3-7.4 mg/l (daphnia magna)
EC50/72h	0.46-4.3 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>1-<10 mg/l (piscis)
	19.03-33.53 mg/l (lem)

(Contd. on page 11)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name: Marble Filler 1000 Transparent Waterclear**

(Contd. of page 10)

LC50/72h	3.24-4.99 mg/l (pimephales promelas) 6.75-14.5 mg/l (Pimephales promelas) 58.75-95.32 mg/l (poecilia reticulata) 4.9 mg/l (algae)
<b>1330-20-7 xylene (mix)</b>	
EC50/24h	>175 mg/l (bacteria) 165 mg/l (daphnia magna)
EC50	10 mg/l (bacteria)
IC50	96 mg/l (BES) 1 mg/l (daphnia magna)
LC50	2 mg/l (piscis)
LC50/24h	32 mg/l (Iepomis macrochirus)
IC50/72h	2.2 mg/l (algae) 3.3 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	3.82 mg/l (daphnia magna)
NOEC	0.96-1.17 mg/l (daphnia magna) >1.3 mg/l (Oncorhynchus mykiss) 0.44 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50/72h	4.7 mg/l (Pseudokirchneriella subcapitata) 2.2 mg/l (selenastrum capricornutum) (OECD 201)
LC50/96h	16.9 mg/l (carp) 1.57 mg/l (Cyprinus carpio) 3.77-13.5 mg/l (piscis) 20.9 mg/l (Iepomis macrochirus) 7.6 mg/l (Oncorhynchus mykiss) 13.4 mg/l (pimephales promelas)
<b>104810-47-1 poly(oxy-1,2-ethanediyl), <math>\alpha</math>-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-<math>\omega</math>-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-</b>	
EC50	>1,000 mg/l (BES) (OECD 209)
EC50/48h	4 mg/l (daphnia magna)
LC 0	>1,000 mg/l (Eisenia fetida ( Regenwürmer))
NOEC	100 mg/kg (Eisenia fetida ( Regenwürmer))
NOEC/21d	0.78 mg/l (daphnia magna) (OECD 202)
EC10	10 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50/72h	>100 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC50/96h	2.8 mg/l (Oncorhynchus mykiss) (OECD 203; ISO 7346; 84/449/EWG, C.1)
<b>108-31-6 maleic anhydride</b>	
EC50/24h	316-330 mg/l (daphnia magna)
EC50	77 mg/l (daphnia magna)
EC10/18h	44.6 mg/l (pseudomonas putida)
EC50/48h	42.81 mg/l (daphnia magna) (OECD 202)
ErC50/72h	74.35 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOELR/72h	150 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	10 mg/l (daphnia magna)

(Contd. on page 12)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name: Marble Filler 1000 Transparent Waterclear**

(Contd. of page 11)

EC50/72h	29 mg/l (Desmodemus subspicatus) 74.32 mg/l (Pseudokirchneriella subcapitata) >150 mg/l (Selenastrum capricornutum)
LC50/96h	75 mg/l (Iepomis macrochirus) 75 mg/l (Oncorhynchus mykiss)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

- **Uncleaned packaging:**
- **Recommendation:** Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
- **Recommended cleansing agents:** Alcohol

**SECTION 14: Transport information**

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN3269
- **14.2 UN proper shipping name**
- **ADR** 3269 POLYESTER RESIN KIT
- **IMDG, IATA** POLYESTER RESIN KIT

· **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 3 (F3) Flammable liquids.

(Contd. on page 13)

## Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name: Marble Filler 1000 Transparent Waterclear**

(Contd. of page 12)

· <u>Label</u>	3
· <u>IMDG, IATA</u>	
	
· <u>Class</u>	3 Flammable liquids.
· <u>Label</u>	3
· <b>14.4 Packing group</b>	
· <u>ADR, IMDG, IATA</u>	III
· <b>14.5 Environmental hazards:</b>	
· <u>Marine pollutant:</u>	No
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· <u>Hazard identification number (Kemler code):</u>	-
· <u>EMS Number:</u>	F-E, S-D
· <u>Stowage Category</u>	A
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <u>Transport/Additional information:</u>	
· <u>ADR</u>	
· <u>Limited quantities (LQ)</u>	5L
· <u>Excepted quantities (EQ)</u>	Code: E0 Not permitted as Excepted Quantity
· <u>Transport category</u>	3
· <u>Tunnel restriction code</u>	E
· <u>IMDG</u>	
· <u>Limited quantities (LQ)</u>	5L
· <u>Excepted quantities (EQ)</u>	Code: See SP340
· <u>UN "Model Regulation":</u>	UN 3269 POLYESTER RESIN KIT, 3, III

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 14)

EU

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name: Marble Filler 1000 Transparent Waterclear**

(Contd. of page 13)

· REGULATION (EU) 2019/1148· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 400.8 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Department issuing SDS: Laboratory· Date of previous version: 13.10.2023· Version number of previous version: 5

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 SVHC: Substances of Very High Concern  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Resp. Sens. 1: Respiratory sensitisation – Category 1

(Contd. on page 15)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.10.2023

Version number 6 (replaces version 5)

Revision: 27.10.2023

**Trade name: Marble Filler 1000 Transparent Waterclear**

(Contd. of page 14)

Skin Sens. 1: Skin sensitisation – Category 1  
Skin Sens. 1A: Skin sensitisation – Category 1A  
Repr. 1B: Reproductive toxicity – Category 1B  
Repr. 2: Reproductive toxicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EU