

e-mail info@akemi.de

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

PLATINUM Clear Liquid P+ · Trade name:

· Article number: 10726, 10742, 11093 5061-A085-A00M-XSMX · UFI:

 1.2 Relevant identified uses of the substance or mixture and

No further relevant information available. uses advised against

· Application of the substance / the

mixture Adhesives

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH Tel. +49(0)911-642960 Fax. +49(0)911-644456

Lechstrasse 28 D 90451 Nürnberg

· Further information obtainable

Laboratory

1.4 Emergency telephone

number: Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

H226 Flammable liquid and vapour. Flam. Liq. 3

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.

Aguatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008

· Hazard pictograms

The product is classified and labelled according to the CLP regulation.







GHS07 GHS08 GHS02

· Signal word Danger

· Hazard-determining components of

labelling: styrene

methacrylic acid

· Hazard statements H226 Flammable liquid and vapour.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)



Page 2/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

Trade name: PLATINUM Clear L	iquid P+	
		(Contd. of page 1)
· Precautionary statements	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read carefully and follow all instructions.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260	Do not breathe vapours.
	P273	Avoid release to the environment.
	P280	Wear protective gloves / eye protection.
	P303+P361+P3	353 IF ON SKIN (or hair): Take off immediately all contaminated
		clothing. Rinse skin with water [or shower].
	P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes.
		Remove contact lenses, if present and easy to do. Continue rinsing.
	P312	Call a POISON CENTER/doctor if you feel unwell.
	P403+P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional information:	Contains methy	l methacrylate, octabenzone. May produce an allergic reaction.
2.3 Other hazards		
· Results of PBT and vPvB asses		
· <u>PBT:</u>	Not applicable.	
· <u>vPvB:</u>	Not applicable.	

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture: consisting of the following components.

Booonption.	Wilklard. Concluding of the following compensation.	
· Dangerous components:		
CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32	styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	25-50%
CAS: 79-41-4 EINECS: 201-204-4 Index number: 607-088-00-5 Reg.nr.: 01-2119463884-26-XXXX	methacrylic acid Skin Corr. 1A, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 1 %	1-5%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<1%
CAS: 38668-48-3 EINECS: 254-075-1 Reg.nr.: 01-2119980937-17	1,1'-(p-tolylimino)dipropan-2-ol Acute Tox. 2, H300 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	<1%
CAS: 1843-05-6 EINECS: 217-421-2 Reg.nr.: 01-2119557833-30-0000	octabenzone Skin Sens. 1B, H317	<1%
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

(Contd. on page 3)



Page 3/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

Trade name: PLATINUM Clear Liquid P+

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Take affected persons out into the fresh air.

Position and transport stably in side position.

Symptoms of poisoning may even occur after several hours; therefore medical

observation for at least 48 hours after the accident.

· After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm.

Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for

transportation.

· After skin contact: If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist,

consult a doctor.

· <u>After swallowing:</u> If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and

delayed

Headache Dizziness Dizziness

Breathing difficulty Profuse sweating

Nausea

· Hazards Danger of impaired breathing.

 4.3 Indication of any immediate medical attention and special

treatment needed If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· <u>Suitable extinguishing agents:</u> CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

· For safety reasons unsuitable

extinguishing agents:

Water with full jet

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO) Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded,

e.g.:

Hydrogen cyanide (HCN)

5.3 Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Mount respiratory protective device.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage

system.

(Contd. on page 4)



Page 4/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

Trade name: PLATINUM Clear Liquid P+

(Contd. of page 3)

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and

emergency procedures

Ensure adequate ventilation Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

• <u>6.2 Environmental precautions:</u> Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

• 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

<u>handling</u> Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than

air).

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and

<u>explosion protection:</u> Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

store only in the original receptacle.

Prevent any seepage into the ground.

· Information about storage in one

common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

· Further information about storage

conditions:

Store receptacle in a well ventilated area.

Protect from frost.

Keep container tightly sealed.

· Storage class:

7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)



Page 5/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

	PLATINUM Clear Liquid P+		(Contd. of page
			——————————————————————————————————————
SECTION	8: Exposure controls/perso	nal protection	
8.1 Contro	ol parameters		
	s with limit values that require	monitoring at the workplace:	
80-62-6 m	ethyl methacrylate		
	ort-term value: 100 ppm		
	ng-term value: 50 ppm		
<u>DNELs</u>			
100-42-5			
Oral	DNEL (Langzeit-wiederholt)	2.1 mg/kg bw/day (BEV)	
Dermal	DNEL (Langzeit-wiederholt)	, , ,	
		343 mg/kg bw/day (BEV)	
Inhalative	DNEL (Kurzzeit-akut)	289-306 mg/m³ Air (ARB)	
	DNEL (Lauren Starte Lauren)	174.25-182.75 mg/m³ Air (BEV)	
	DNEL (Langzeit-wiederholt)	85 mg/m³ Air (ARB)	
70 44 4 m	ethacrylic acid	10.2 mg/m³ Air (BEV)	
Dermal	DNEL (Langzeit-wiederholt)	4.25 mg/kg hw/day (APR)	
Demiai	DIVEE (Langzen-wiederholt)	2.55 mg/kg bw/day (ARD)	
Inhalative	DNEL (Langzeit-wiederholt)	29.6-88 mg/m³ Air (ARB)	
mididavo	Ditz (zangzak madamak)	6.3-6.55 mg/m³ Air (BEV)	
80-62-6 m	ethyl methacrylate	0.0 0.00 mg/m / m (2_1)	
Oral	DNEL (Kurzzeit-akut)	0.25 mg/kg bw/day (BEV)	
Dermal	DNEL (Kurzzeit-akut)	1.5 mg/kg bw/day (ARB)	
		1.5 mg/kg bw/day (BEV)	
	DNEL (Langzeit-wiederholt)	1.5-13.67 mg/kg bw/day (ARB)	
		1.5-8.2 mg/kg bw/day (BEV)	
Inhalative	DNEL (Kurzzeit-akut)	29.6-416 mg/m³ Air (ARB)	
		6.3-104 mg/m³ Air (BEV)	
	DNEL (Langzeit-wiederholt)	208 mg/m³ Air (ARB)	
		74.3-104 mg/m³ Air (BEV)	
	3 1,1'-(p-tolylimino)dipropa		
Oral	DNEL (Langzeit-wiederholt)	0.25 mg/kg bw/day (BEV)	
Dermal	DNEL (Langzeit-wiederholt)	5 ° ° ° ° ° ° ° ° ° ° ° ° ° ° ° ° ° ° °	
Inholotice	DNEL (Longreit wiederk - 14)	0.3 mg/kg bw/day (BEV)	
ııınalative	DNEL (Langzeit-wiederholt)	2.47 mg/m³ Air (ARB) 0.4 mg/m³ Air (BEV)	
18/3 NE G	octabenzone	U.4 Mg/M All (DEV)	
1843-05-6 Oral	DNEL (Langzeit-wiederholt)	0.9 mg/kg bw/day (BEV)	
Dermal	DNEL (Langzeit-wiederholt)		
Dominal	DITEL (Langzon-Wiedenholt)	0.9 mg/kg bw/day (BEV)	
Inhalativa	DNEL (Langzeit-wiederholt)	6.6 mg/m³ Air (ARB)	
Illinalalive	DIVLE (Lanuzen-wiedennon)		

EU



Page 6/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

		(Contd. of page
PNECs		, , , ,
100-42-5 styre	ne	
PNEC (wässrig	ı) 5 mg/l (KA)	
_	0.014 mg/l (MW)	
	0.028 mg/l (SW)	
	0.04 mg/l (WAS)	
PNEC (fest)	0.2 mg/kg Trockengew (BO)	
()	0.307 mg/kg Trockengew (MWS)	
	0.614 mg/kg Trockengew (SWS)	
79-41-4 metha		
PNEC (wässrig		
, ,	0.82 mg/l (MW)	
	0.82 mg/l (SW)	
PNEC (fest)	1.2 mg/kg Trockengew (BO)	
` '	I methacrylate	
PNEC (wässrig	<u> </u>	
, ,	0.094 mg/l (MW)	
	0.94 mg/l (SW)	
	0.15-0.94 mg/l (WAS)	
PNEC (fest)	1.47 mg/kg Trockengew (BO)	
,	0.102 mg/kg Trockengew (MWS)	
	10.2 mg/kg Trockengew (SWS)	
38668-48-3 1,1	'-(p-tolylimino)dipropan-2-ol	
PNEC (wässrig	ı) 199.5 mg/l (KA)	
	0.0017 mg/l (MW)	
	0.017 mg/l (SW)	
	0.17 mg/l (WAS)	
PNEC (fest)	0.005 mg/kg Trockengew (BO)	
, ,	0.00782 mg/kg Trockengew (MWS)	
	0.0782 mg/kg Trockengew (SWS)	
1843-05-6 octa	abenzone	
PNEC (wässrig	1) 1 mg/l (KA)	
	0.0052 mg/l (MW)	
	0.052 mg/l (SW)	
	0.52 mg/l (WAS)	
PNEC (fest)	66.8 mg/kg Trockengew (BO)	
	10 mg/kg Trockengew (MWS)	
	100 mg/kg Trockengew (SWS)	
Additional infor	mation: The lists valid during the making were used as basis.	
8.2 Exposure		
	gineering controls No further data; see item 7.	
	ection measures, such as personal protective equipment	
measures:	tive and hygienic Do not eat, drink, smoke or sniff while working.	

Clean skin thoroughly immediately after handling the product.

(Contd. on page 7)



(Contd. of page 6)

Page 7/15

· Hand protection

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

Trade name: PLATINUM Clear Liquid P+

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Respiratory protection: Short term filter device:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Preventive skin protection by use of skin-protecting agents is recommended.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Skin protection agent recommendation for preventive skin shelter without use of protective gloves:

ARRETIL (http://www.stoko.com)

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

Kresto Classic (http://debstoko.com)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (http://www.stoko.com)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).

Fluorocarbon rubber (Viton) · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level \leq 6, 480 min

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

(Contd. on page 8)



(Contd. of page 7)

Page 8/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

Trade name: PLATINUM Clear Liquid P+

· For the permanent contact gloves made of the following materials are

suitable:

Fluorocarbon rubber (Viton) Vitoject (KCL, Art No. 890)

· As protection from splashes gloves made of the following materials are

suitable:

Fluorocarbon rubber (Viton) Vitoject (KCL, Art_No. 890)

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

Nitrile rubber, NBR

Dermatril (KCL, Art_No. 740, 741, 742) Camatril (KCL, 730, 731, 732, 733)

· Not suitable are gloves made of

the following materials:

Natural rubber, NR Chloroprene rubber, CR Leather gloves

Strong material gloves

Eye/face protection

Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Light yellow · Odour: Specific type · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling range 145.2 °C

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: 1.2 Vol % 8.9 Vol % · Upper: 31-32 °C · Flash point: 480 °C · Ignition temperature:

· Decomposition temperature: Not determined. Not determined. Not applicable

· Viscosity:

· Kinematic viscosity at 20 °C 3,400 s (DIN 53211/4) · Dynamic: Not determined. Not applicable

Solubility

Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 6 hPa

· Density and/or relative density

· Density at 20 °C: 1.08 g/cm3 · Relative density · Vapour density Not determined.

Not determined.

(Contd. on page 9)



Page 9/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

Trade name: PLATINUM Clear Liquid P+

(Contd. of page 8)

9.2 Other information

· Appearance:

· <u>Form:</u> Fluid

· Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Solvent content:

· Organic solvents: 33.6 %
· Solids content: 1.4 %

Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures

Void · Pyrophoric liquids Void

Pyrophoric solids Void

· Self-heating substances and mixtures

Void

 $\cdot \, \underline{\text{Substances and mixtures, which emit flammable}} \,$

gases in contact with water

Void

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

Void

SECTION 10: Stability and reactivity

· <u>10.1 Reactivity</u> No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous

<u>reactions</u> Exothermic polymerisation.

Reacts with peroxides and other radical forming substances.

Reacts with acids.
Reacts with strong alkali.

• 10.4 Conditions to avoid
• 10.5 Incompatible materials:

No further relevant information available.

No further relevant information available.

· 10.6 Hazardous decomposition

products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

(Contd. on page 10)



Page 10/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

Trade name: PLATINUM Clear Liquid P+ (Contd. of page 9) Hydrogen cyanide (prussic acid)

SECTION 11: Toxicological information

· Acute toxic		Based on available data, the classification criteria are not met.
· <u>LD/LC50</u> v	/alues rele	vant for classification:
	te Toxicity	y Estimates)
Oral	LD50	>2,859-<17,645 mg/kg (rat)
Dermal	LD50	25,589-51,177 mg/kg
Inhalative	LC50/4 h	34 mg/l
100-42-5	styrene	
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)
Inhalative	LC50/4h	9.5 mg/m3 (mouse)
		11,800 mg/m3 (rat)
	LC50/4 h	11.8 mg/l (rat)
	NOAEC	4.34 mg/l (rat)
79-41-4 m	ethacrylic	acid
Oral	LD50	1,320 mg/kg (rat)
Dermal	LD50	500-1,000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
	LC50/1h	7.1 mg/l (rat)
80-62-6 methyl methacrylate		
Oral	LD50	7,872 mg/kg (rat) (OECD 401)
	NOAEL	2,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative		4,632 mg/m3 (rat)
	LC50/4 h	29.8 mg/l (rat)
	NOAEL	25 mg/m³ (rat)
38668-48-	3 1,1'-(p-t	olylimino)dipropan-2-ol
Oral	LD50	>25-<200 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
1843-05-6	octabenz	one
Oral	LD50	>5,000 mg/kg (rat)
Dermal	I DEO	>5 000 ma/kg (robbit)

>5,000 mg/kg (rabbit) Dermal LD50

Skin corrosion/irritation Causes skin irritation.

Causes serious eye irritation. · Serious eye damage/irritation

Based on available data, the classification criteria are not met. · Respiratory or skin sensitisation Based on available data, the classification criteria are not met. · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity

· Reproductive toxicity Suspected of damaging the unborn child.

· STOT-single exposure May cause respiratory irritation.

· STOT-repeated exposure Causes damage to the hearing organs through prolonged or repeated exposure.

Based on available data, the classification criteria are not met. Aspiration hazard

(Contd. on page 11)



Page 11/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

Trade name: PLATINUM Clear Liquid P+

11.2 Information on other hazards

(Contd. of page 10)

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

	A		
-	· Aquatic toxicity:		
100-42-5 sty			
EC50/96h	6.3 mg/l (Pseudokirchneriella subcapitata)		
EC50	500 mg/l (BES) (ISO Vorschrift 8192-1986 E)		
	5.5 mg/l (Photobac. phosphoreum)		
IC50/72h	4.9 mg/l (green alge)		
	1.4 mg/l (selenastrum capricornutum)		
IC5/8d	>200 mg/l (Scenedesmus quadricauda)		
EC10/16h	72 mg/l (pseudomonas putida)		
EC50/16h	>72 mg/l (pseudomonas putida)		
EC50/8d	>200 mg/l (Scenedesmus quadricauda)		
EC50/72u	>1-<10 mg/l (green alge)		
EC20/0.5h	140 mg/l (BES) (OECD 209)		
NOEC/21d	1.01 mg/l (daphnia magna)		
EC10	0.28 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050)		
EC50/48h	0.56 mg/l (green alge)		
	3.3-7.4 mg/l (daphnia magna)		
EC50/72h	0.46-4.3 mg/l (Pseudokirchneriella subcapitata)		
LC50/96h	>1-<10 mg/l (piscis)		
	19.03-33.53 mg/l (lem)		
	3.24-4.99 mg/l (pimephales promelas)		
	6.75-14.5 mg/l (Pimephales promelas)		
	58.75-95.32 mg/l (poecilia reticulata)		
LC50/72h	4.9 mg/l (green alge)		
79-41-4 met	hacrylic acid		
IC50/72h	0.59 mg/l (Selenastrum capricornutum)		
EC10/16h	100 mg/l (Microcystis aeruginosa)		
NOELR/21d	53 mg/l (daphnia magna)		
EC50/48h	>130 mg/l (daphnia magna)		
EC50/72h	45 mg/l (green alge)		
LC50/96h	85 mg/l (Oncorhynchus mykiss)		
80-62-6 met	hyl methacrylate		
EC50/96h	170 mg/l (Pseudokirchneriella subcapitata)		
EC50/48h	69 mg/l (daphnia magna) (OECD 202)		
EC0	100 mg/l (pseudomonas putida)		
NOEC	9.4 mg/kg (Danio rerio.) (OECD 210)		
NOEC	>100 mg/l (Selenastrum capricornutum)		
NOEC/21d	37 mg/l (daphnia magna) (OECD 202)		
	(Contd. on page 12)		

Conta. on page 1



Page 12/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

	Trade name:	PLATINUM	Clear Liquid P+
--	-------------	----------	-----------------

		(Contd. of page 11)
EC50/72h	>110 mg/l (Selenastrum capricornutum)	

	• (,
LC50/96h	153.9-341.8 mg/l (lem)		
	>79 mg/l (Oncorhynchus	mykiss) (C	DECD 203)

125-275 mg/l (pimephales promelas)

326.4-426.9 mg/l (poecilia reticulata)

38668-48-3 1,1'-(p-tolylimino)dipropan-2-ol

EC50/48h 28.8 mg/l (daphnia magna) (OECD 202)

EC20/0.5h >1,995 mg/l (BES) (OECD 209)

EC50/72h 245 mg/l (Desmodesmus subspicatus) (OECD 201)

LC50/96h 17 mg/l (Brachydanio rerio)

1843-05-6 octabenzone

EC50/24h 52 mg/l (daphnia magna)

IC50 >100 mg/l (BES)

52 mg/l (daphnia magna)

LC50 >100 mg/l (Brachydanio rerio) EC50/48h >0.0038 mg/l (daphnia magna)

EC20/3h >100 mg/l (BES)

EC50/72h >100 mg/l (Scenedesmus subspicatus)

LC50/96h >100 mg/l (Brachydanio rerio) (OECD 203)

12.2 Persistence and

degradability
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

12.5 Results of PBT and vPvB assessment

 $\begin{array}{ll} \cdot \underline{\mathsf{PBT:}} & \mathsf{Not \ applicable.} \\ \cdot \underline{\mathsf{vPvB:}} & \mathsf{Not \ applicable.} \end{array}$

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

· Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for

water

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must be specially treated adhering to official regulations.

Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

· European waste catalogue

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND
	INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)

20 01 27* paint, inks, adhesives and resins containing hazardous substances

Uncleaned packaging:

Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

(Contd. on page 13)



Page 13/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

Trade name: PLATINUM Clear Liquid P+ (Contd. of page 12) Recommended cleansing agents: Alcohol **SECTION 14: Transport information** · 14.1 UN number or ID number · ADR, IMDG, IATA UN3269 14.2 UN proper shipping name 3269 POLYESTER RESIN KIT · IMDG, IATA POLYESTER RESIN KIT · 14.3 Transport hazard class(es) · ADR · Class 3 (F3) Flammable liquids. · Label · IMDG, IATA · Class 3 Flammable liquids. · Label · 14.4 Packing group · ADR, IMDG, IATA · 14.5 Environmental hazards: · Marine pollutant: · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): · EMS Number: F-E,S-D Stowage Category 14.7 Maritime transport in bulk according to IMO Not applicable. instruments · Transport/Additional information: · ADR · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Transport category 3 · Tunnel restriction code Ε Without hardener component: no dangerous goods < 450 l · Remarks: · IMDG · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 14)



Page 14/15

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

Trade name: PLATINUM Clear Liquid P+

(Contd. of page 13)

· Remarks: Without hardener component: no dangerous goods < 30 l

· IATA

· Remarks: Without hardener component: 3/III UN 1866 Resin Solution

· UN "Model Regulation": UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed. Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier

requirements

5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier

50.000 t requirements

· REGULATION (EC) No 1907/2006

Conditions of restriction: 3 ANNEX XVII

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning juveniles must be observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 362.8 g/l

· 15.2 Chemical safety

A Chemical Safety Assessment has not been carried out. assessment:

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 15)



AKEMI®

(Contd. of page 14)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.01.2023 Version number 8 (replaces version 7) Revision: 24.01.2023

Trade name: PLATINUM Clear Liquid P+

· Department issuing SDS: Laboratory · Date of previous version:

· Version number of previous version:

· Abbreviations and acronyms:

24.01.2023

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European

Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3