

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Transformer MAX**
- Article number: 12042, 12043, 12044, 12049
- UFI: J3R0-A0EU-Q00F-SG7G

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Protective impregnation

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
- Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

- Flam. Liq. 3 H226 Flammable liquid and vapour.
- Eye Irrit. 2 H319 Causes serious eye irritation.
- STOT SE 3 H336 May cause drowsiness or dizziness.
- Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
Kohlenwasserstoffe, C8-C9, Isoalkane
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

Hazard statements

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

Trade name: Transformer MAX

(Contd. of page 1)

P261	Avoid breathing vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional information:	EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards**· Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.**· Determination of endocrine-disrupting properties**

For information on endocrine disrupting properties see section 11.

SECTION 3: Composition/information on ingredients**· 3.2 Mixtures**· **Description:** Mixture: consisting of the following components.**· Dangerous components:**

EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066	25-50%
EC number: 932-020-9 Reg.nr.: 01-2119548395-31	Kohlenwasserstoffe, C8-C9, Isoalkane Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336 EUH066	<10%
CAS: 5593-70-4 EINECS: 227-006-8 Reg.nr.: 01-2119967423-33	tetra-n-butoxytitanium Flam. Liq. 3, H226 Eye Dam. 1, H318 Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-5%
CAS: 67-56-1 EINECS: 200-659-6 Index number: 603-001-00-X Reg.nr.: 01-2119433307-44	methanol Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %	<1%

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

Trade name: Transformer MAX

(Contd. of page 2)

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

- General information: Take affected persons out of danger area and lay down. Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints. In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately rinse with water. If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Rinse out mouth and then drink plenty of water. If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media**

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

· 5.2 Special hazards arising from the substance or mixtureIn case of fire, the following can be released:
Carbon monoxide (CO)**· 5.3 Advice for firefighters**

- Protective equipment: Mount respiratory protective device. Wear fully protective suit.
- Additional information Cool endangered receptacles with water spray. Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Prevent seepage into sewage system, workpits and cellars. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

Trade name: Transformer MAX

(Contd. of page 3)

See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Keep receptacles tightly sealed.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Information about storage in one common storage facility:

Store away from foodstuffs.

Further information about storage conditions:

Protect from frost.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

Storage class:

3

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****67-56-1 methanol**

IOELV	Long-term value: 260 mg/m ³ , 200 ppm Skin
-------	--

DNELs**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics**

Oral	DNEL (Langzeit-wiederholt)	125 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	208 mg/kg bw/day (ARB)
		125 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	871 mg/m ³ Air (ARB)
		185 mg/m ³ Air (BEV)

Kohlenwasserstoffe, C8-C9, Isoalkane

Oral	DNEL (Langzeit-wiederholt)	699 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	773 mg/kg bw/day (ARB)
		699 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	2,035 mg/m ³ Air (ARB)
		608 mg/m ³ Air (BEV)

5593-70-4 tetra-n-butoxytitanium

Oral	DNEL (Langzeit-wiederholt)	3.75 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	37.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	500 mg/m ³ Air (ARB)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

Trade name: Transformer MAX

(Contd. of page 4)

		38 mg/m ³ Air (BEV)
67-56-1 methanol		
Oral	DNEL (Kurzzeit-akut)	4 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	4 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	20 mg/kg bw/day (ARB)
		4 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	20 mg/kg bw/day (ARB)
		4 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	130 mg/m ³ Air (ARB)
		26 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	130 mg/m ³ Air (ARB)
		26 mg/m ³ Air (BEV)

· PNECs

5593-70-4 tetra-n-butoxytitanium

PNEC (wässrig)	105 mg/l (KA)
	0.059 mg/l (MW)
	0.59 mg/l (SW)
	2.25 mg/l (WAS)
PNEC (fest)	0.017 mg/kg Trockengew (BO)
	0.048 mg/kg Trockengew (MWS)
	0.482 mg/kg Trockengew (SWS)

67-56-1 methanol

PNEC (wässrig)	100 mg/l (KA)
	2.08 mg/l (MW)
	20.8 mg/l (SW)
	1,540 mg/l (WAS)
PNEC (fest)	100 mg/kg Trockengew (BO)
	7.7 mg/kg Trockengew (MWS)
	77 mg/kg Trockengew (SWS)

· Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Respiratory protection:

Short term filter device:
Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Protective gloves

(Contd. on page 6)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

Trade name: Transformer MAX

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

· As protection from splashes gloves made of the following materials are suitable:

Butoject (KCL, Art_No. 897, 898)

Butyl rubber, BR

· Not suitable are gloves made of the following materials:

Strong material gloves

Synthetic rubber gloves

· Eye/face protection

Tightly sealed goggles

· Body protection:

Solvent resistant protective clothing

SECTION 9: Physical and chemical properties· **9.1 Information on basic physical and chemical properties**· General Information· Colour:

Colourless

· Odour:

Specific type

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

110-190 °C

· Flammability

Not applicable.

· Lower and upper explosion limit· Lower:

2.1 Vol %

· Upper:

11.5 Vol %

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

Trade name: Transformer MAX

(Contd. of page 6)

· <u>Flash point:</u>	27 °C
· <u>Auto-ignition temperature:</u>	460 °C
· <u>Decomposition temperature:</u>	Not determined.
· <u>pH</u>	Not determined.
· <u>Viscosity:</u>	
· <u>Kinematic viscosity</u>	Not determined.
· <u>Dynamic:</u>	Not determined.
· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Partition coefficient n-octanol/water (log value)</u>	Not determined.
· <u>Vapour pressure:</u>	Not determined.
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	0.89 g/cm ³
· <u>Relative density</u>	Not determined.
· <u>Vapour density</u>	Not determined.

· 9.2 Other information

· <u>Appearance:</u>	
· <u>Form:</u>	Fluid
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <u>Solvent content:</u>	
· <u>Organic solvents:</u>	39.9 %
· <u>Change in condition</u>	
· <u>Evaporation rate</u>	Not determined.

· <u>Information with regard to physical hazard classes</u>	
· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Void
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Flammable liquid and vapour.
· <u>Flammable solids</u>	Void
· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	Void
· <u>Substances and mixtures, which emit flammable gases in contact with water</u>	Void
· <u>Oxidising liquids</u>	Void
· <u>Oxidising solids</u>	Void
· <u>Organic peroxides</u>	Void
· <u>Corrosive to metals</u>	Void
· <u>Desensitised explosives</u>	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· <u>Thermal decomposition / conditions to be avoided:</u>	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

Trade name: Transformer MAX

(Contd. of page 7)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	18,797 mg/kg (rat)
Dermal	LD50	56,391 mg/kg

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Oral	LD50	5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	4,951 mg/l (rat) (OECD 403)

Kohlenwasserstoffe, C8-C9, Isoalkane

Oral	LD50	>7,100 mg/kg (rat)
Dermal	LD50	>2,200 mg/kg (rabbit)

5593-70-4 tetra-n-butoxytitanium

Oral	LD50	3,122 mg/kg (rat)
Dermal	LD50	5,300 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (rat)

67-56-1 methanol

Oral	LD50	100 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)
Inhalative	LC50/4 h	300 mg/kg (rat) 128.2 mg/l (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

· **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information· **12.1 Toxicity**

- **Aquatic toxicity:**

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

EL50/48h	>22-<46 mg/l (daphnia magna)
----------	------------------------------

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

Trade name: Transformer MAX

(Contd. of page 8)

EL50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	>10-<30 mg/l (Oncorhynchus mykiss)
NOELR/72h	<1 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	0.317 mg/l (daphnia magna)
NOELR/28d	0.182 mg/l (Oncorhynchus mykiss)

Kohlenwasserstoffe, C8-C9, Isoalkane

EC50/48h	2.4 mg/l (daphnia magna)
NOELR/72h	6.3 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	1 mg/l (daphnia magna)
NOELR/28d	0.46 mg/l (Oncorhynchus mykiss)
EC50/72h	10 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	18.4 mg/l (Oncorhynchus mykiss)

5593-70-4 tetra-n-butoxytitanium

EC50/96h	225 mg/l (algae)
EC50/48h	1,300 mg/l (daphnia magna)
NOEC/21d	4 mg/l (daphnia magna)
EC10	134 mg/l (algae) 650 mg/l (bacteria)
EC50/72h	225 mg/l (algae)
LC50/96h	1,740-2,300 mg/l (piscis)

67-56-1 methanol

EC50/96h	22,000 mg/l (Pseudokirchneriella subcapitata)
IC50	>1,000 mg/l (BES)
EC50/48h	>10,000 mg/l (daphnia magna)
LC50/96h	13,500-17,600 mg/l (lem) 19,500-20,700 mg/l (Oncorhynchus mykiss) 28,200 mg/l (pimephales promelas)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· PBT: Not applicable.

· vPvB: Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

Trade name: Transformer MAX

(Contd. of page 9)

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information· **14.1 UN number or ID number**· ADR, IMDG, IATA UN1993· **14.2 UN proper shipping name**

· ADR 1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics, METHANOL)

· IMDG, IATA FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics, METHANOL)

· **14.3 Transport hazard class(es)**· ADR

· Class 3 (F1) Flammable liquids.

· Label 3

· IMDG, IATA

· Class 3 Flammable liquids.

· Label 3

· **14.4 Packing group**· ADR, IMDG, IATA III· **14.5 Environmental hazards:**· Marine pollutant: No· **14.6 Special precautions for user**

· Hazard identification number (Kemler code): Warning: Flammable liquids.
30

· EMS Number: F-E, S-E

· Stowage Category A

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· Transport category 3

· Tunnel restriction code D/E

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

Trade name: Transformer MAX

(Contd. of page 10)

· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLOALKANES, <2% AROMATICS, METHANOL), 3, III

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I
None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII
Conditions of restriction: 3, 69

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 355.5 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.11.2023

Version number 11 (replaces version 10)

Revision: 07.11.2023

Trade name: Transformer MAX

(Contd. of page 11)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

<ul style="list-style-type: none"> · <u>Department issuing SDS:</u> · <u>Date of previous version:</u> · <u>Version number of previous version:</u> · <u>Abbreviations and acronyms:</u> 	<p>Laboratory 09.12.2022 10</p> <p>ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3</p>
--	--

EU